



THUAN PHONG COMPANY LTD.

Address: 159 Binh gia Street, Ward 8, Vung Tau city, Vietnam

Phonne: 84-64-3859 784 ; Fax: 84-64-3854 093

Email: thuanphongco@hcm.vnn.vn ; Website: www.thuanphongco.com



QUALITY MANAGEMENT SYSTEM

CTP-3 ANTIFOAM

MATERIAL SAFETY DATA SHEET

Issue date: 03/2009

1. PRODUCT AND MANUFACTURER IDENTIFICATION

Trade Name: **ANTIFOAM CTP-3**
Product Family: Silicone
Product Description: Foam Control
Application: Excellent stabilise and maximum foam control in highly alkaline systems, for hydrocarbon systems or water systems where water systems hydrocarbon is the predominant phase and high temperature environments

Manufacturer / Supplier: THUAN PHONG Co., Ltd.
Add: 159 Binh Gia St, Ward 8, Vung Tau City, S.R. Viet Nam
Contact: Tel: 84-64-3859784, Fax: 84-64-3854093

2. COMPOSITION INFORMATION

<u>Component</u>	<u>Content</u> (% by weight)	<u>Hazardous Classification</u>
Polyalkylsiloxane	28 – 32	
Polyether modified silicone fluid	28 – 32	
Silica (or Silicon dioxide)	5 – 10	
Emulsifying agent	3	
Antiseptics	1	
Water	22 – 25	
Additives	5	
Total	100%	

3. HAZARDS IDENTIFICATION

Highly flammable.
Toxic by inhalation, in contact with skin and if swallowed.

4. FIRST-AID MEASURES

EYE CONTACT

Promptly wash opened eye for several minutes under running water. Get medical attention promptly if symptoms occur after washing.

SKIN CONTACT

Wash immediately with water and soap. Get medical attention promptly if symptoms occur after washing.

INHALATION

Remove victim immediately from source of exposure. Supply fresh air. Get medical attention.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention immediately!

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Water spray, CO₂, foam, extinguishing powder, sand etc.

SPECIAL FIRE FIGHTING PROCEDURES

Use supplied air respirator if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out.

HAZARDOUS COMBUSTION PRODUCTS
Carbon monoxide (CO), Carbon dioxide (CO₂)
PROTECTIVE MEASURES IN FIRE
Full protective equipment including suitable respiratory protection.

6. ACCIDENTAL RELEASE MEASURES

Evacuate people on the leeward.
Keep people away from the area.
Remove sources of ignition.
Wear proper protective equipment when in work.
Work from the windward side.
Put in an empty container for recovery after preventing spill by sand or sandbags, if the amount of spill is large.
Put in an empty container for recovery after wiping or soaking up in an inert material, if the amount of spill is small.

7. HANDLING AND STORAGE

HANDLING

Wear eye and hand protection when in handling.
Use after well stirring.

STORAGE

Store in a dark, cool place indoors with small temperature changes, with container tightly closed. Be careful as the product freezes at 0°C.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level (explosion-proof general and local exhaust ventilation).

HAND PROTECTION

Use protective gloves made of: rubber, neoprene, nitrile, polyethylene or PVC.

EYE/FACE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

SKIN PROTECTION

Wear protective clothing chemically resistant to this material to prevent any possibility of skin contact

RESPIRATORY PROTECTION

Respiratory protection must be used if air concentration exceeds acceptable level. Use chemical respirator with appropriate organic vapor cartridge.

OTHER PROTECTION

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. No eating or drinking while working with this material. DO NOT SMOKE IN WORK AREA.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Milky White Emulsion
Odor	Slight Smell
Boiling point	100°C
Viscosity @ 20°C, cSt	680 Min.
Specific gravity (H ₂ O=1)	1.005
Solubility in water	Dispersible
pH	6.5 – 9.0
Kinetic viscosity at 25°C	40 – 90 mm ² /s

10. STABILITY AND REACTIVITY

STABILITY

Normally stable at typical use temperatures
No particular stability concerns.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide (CO), Carbon dioxide (CO₂)

11. TOXICOLOGICAL INFORMATION

INGESTION

No data

INHALATION

No data

SKIN CONTACT

Liquid may irritate skin in contact with skin.

EYE CONTACT

Vapor in the eyes may cause smarting

12. ECOLOGICAL INFORMATION

Harmful to aquatic organisms, may cause long-term adverse effects in the environment.

13. DISPOSAL CONSIDERATIONS

AFTER OIL AND WATER ARE SEPARATED, INCINERATION FOR OILS SHOULD BE MADE IN APPROVED CHEMICAL INCINERATOR IN ACCORDANCE WITH REGULATIONS. THE WATER SHOULD BE TREATED AT WASTE UNDER TREATMENT FACILITIES.

14. TRANSPORT INFORMATION

Transport under dark, cool conditions.

The substance is not regarded as a dangerous material for ship and air transportation.

15. REGULATORY INFORMATION

Not applicable

16. OTHER/ADDITIONAL INFORMATIONS

THIS MATERIAL IS DEVELOPED AND MANUFACTURED FOR INDUSTRIAL APPLICATION ONLY.

THE INFORMATION HEREIN IS MADE BASED ON REFERENCES, INFORMATION AND DATA AVAILABLE AT PRESENT. IT MAY BE REVISED NEW INFORMATION IS AVAILABLE. THE DESCRIPTIONS HEREIN ARE FOR NORMAL HANDLING. FOR SPECIAL APPLICATIONS, MAKE SAFETY PROVISIONS SUITABLE TO THEM PRIOR TO USE.